



AUTOMATIC WATER SOFTENER



AUTOMATIC WATER SOFTENER-AWS-1054-255



FEATURES

- On screen display & soft keys for programming at site
- Clear-sight air check for easy brine line troubleshooting
- Top mounted Pentair Autotrol 255 model softener valve with NSF listed material
- Tank adapter permits disconnection from valve without disturbing the resin bed
- Auto refill of brine tank
- Resin volume-28l included
- Corrosion resistant long life, light weight FRP Vessel-10x54

VALVE SPECIFICATIONS

Inlet/outlet	1.25 inch
Service	2 m3/hr.
Backwash	1.35 m3/hr.
Drain Line	½ inch
Brine Line	3/8 inch NPT
Distributor Tube	1.050 inches
Tank Thread	2-1/2-inches – 8, male

SYSTEM SPECIFICATIONS

Turbidity	< 2 NTU
Pressure	1.8-3.5 Bar
Temp. Range	2-40 Deg. C
Chlorine	Nil
Feed TDS	2000 ppm
Salt	Approx. 4.5 Kg per reg.
Resin Qty.	28 Ltrs.



REGISTERED OFFICE &
MANUFACTURING FACILITY

PENTAIR WATER INDIA PVT. LTD
L/52-55, Verna Industrial Estate,
Verna, Salcette, Goa - 403 722.

Phone : +91 832 2883300

Email : customercare.waterindia@pentair.com